

AQUENCE[®]**AQUENCE CASING 7248**Formerly known as
ADHESIN[®] 7248

July 2012

TYPE OF ADHESIVE:

Aqueous

FIELD OF APPLICATION:

Bookbinding > Casing-in

TYPICAL TECHNICAL DATA:

Viscosity: 2,200 cps. Brookfield RVT

pH: 5.0

Color: White

Solids: 59%

PROPERTIES:

Aquence Casing 7248 is a water based adhesive designed for the bookbinding industry. It adheres difficult to bond surfaces, and runs well on Kolbus 40 and 70 casing-in machines. All ingredients in Aquence Casing 7248 are approved under the Federal Regulation 21 CFR 175.105, which relates to incidental contact of adhesives with food.

HANDLING AND APPLICATION:

Aquence Casing 7248 is supplied ready for use. Preferred running temperature is 70-85°F. This adhesive cleans up while wet or dry.

PRECAUTIONS:

Do not mix with other adhesives.

STORAGE CONDITIONS:

Aquence Casing 7248 has a 90 day shelf life. Rotate stock, using oldest first. Keep container covered when not in use to prevent moisture loss and contamination. Do not freeze.

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all marks used are trademarks of Henkel or its affiliates in the U.S. and elsewhere. [®] denotes a trademark registered in the U.S. Patent and Trademark Office.

Henkel Corporation

Tel: 1.888.480.6889

Email: bw.nacustomerservice@henkel.com

www.henkelna.com

