

TYPE:

Hot Melt Adhesive

PHYSICAL PROPERTIES:

Appearance: Light Yellow Solid

Viscosity: Approx. 1550 cps @ 350°F

Approx. 2250 cps @ 325°F

Approx. 3350 cps @ 300°F

Approx. 5250 cps @ 275°F

Approx. 8900 cps @ 250°F

Approx. 16000 cps @ 225°F

Approx. 31225 cps @ 200°F

Lbs./Gallon: Approx. 8.2

Softening Point: Approx. 156°F Mettler

Form: mini slats

Designed for application at 275°F +/- 15°F. Offers excellent adhesion, low odor, good color, low energy use, reduced burn hazard, and less maintenance.

SUGGESTED USES:

Perfect Binding, Heidelberg, Kolbus, Muller-Martini, Wohlenberg and others.

OPERATING CONDITIONS:Running temperature range: 260-290°F Applicator
275°F Premelter**PRECAUTIONS:**

Material is applied hot - appropriate clothing and eye protection should be used. Use with adequate ventilation to remove any hot melt fumes or vapors that are generated. Keep containers and premelters covered to avoid contamination. Rotate stock - first in, first out. Do not mix with other adhesives.

PACKAGE:

1000 lb. cartons.

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be

interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all marks used are trademarks of Henkel or its affiliates in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.