



Revision Number: 001.0

Issue date: 07/29/2011

**1. PRODUCT AND COMPANY IDENTIFICATION**

**Product name:** TECHNOMELT SUPRA 200  
**Product type:** Hotmelt adhesive  
**IDH number:** 1610825  
**Region:** United States  
**Company address:** Henkel Corporation  
 10 FINDERNE AVENUE, SUITE B  
 BRIDGEWATER, NEW JERSEY 08807  
**Contact information:** Customer Service: 1-888-480-6889  
 MEDICAL EMERGENCY Phone: Poison Control Center  
 1-877-671-4608 (toll free) or 1-303-592-1711  
 TRANSPORT EMERGENCY Phone: CHEMTREC  
 1-800-424-9300 (toll free) or 1-703-527-3887  
 Internet: www.henkeln.com

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

<b>Physical state:</b>	Solid	<b>HEALTH:</b>	2
<b>Color:</b>	Yellow	<b>FLAMMABILITY:</b>	1
<b>Odor:</b>	Slight	<b>PHYSICAL HAZARD:</b>	0
		<b>Personal Protection:</b>	See MSDS Section 8

**CAUTION:** MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS.  
 ADHESIVE VAPORS MAY CAUSE SLIGHT IRRITATION OF THE EYES, SKIN OR RESPIRATORY SYSTEM.

**Relevant routes of exposure:** Skin, Inhalation, Eyes

**Potential Health Effects**

**Inhalation:** Dusts from solid adhesive may cause irritation. Continuous breathing of vapors above molten adhesive may irritate mucous membranes.  
**Skin contact:** Solid adhesive has no hazards. Molten adhesive may cause severe burns.  
**Eye contact:** Can cause mechanical irritation if dusts are generated. Fumes released during thermal processing may cause eye irritation. Molten adhesive in eyes will cause severe and permanent damage.  
**Ingestion:** Not expected under normal conditions of use. Expected to be low in toxicity.

**Existing conditions aggravated by exposure:** Eye, skin, and respiratory disorders.

This product is considered not hazardous under 29 CFR 1910.1200 (Hazard Communication).

See Section 11 for additional toxicological information.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Hazardous components	CAS NUMBER	%
Paraffin waxes and Hydrocarbon waxes	8002-74-2	10 - 30

**4. FIRST AID MEASURES**

**Inhalation:** Move to fresh air. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.

<b>Skin contact:</b>	Molten adhesive may cause severe burns. Cool melted product on skin with plenty of water. Do not remove solidified product. No attempt should be made to remove material from skin or to remove contaminated clothing as damaged skin can be easily torn. Cover affected areas with clean sheeting or gauze and seek immediate medical attention.
<b>Eye contact:</b>	If eye contact occurs with molten material immediately cool with water. Do not remove adhesive. Seek medical attention.
<b>Ingestion:</b>	Ingestion of solid adhesive is not expected to be hazardous. If symptoms develop and persist, get medical attention.

## 5. FIRE FIGHTING MEASURES

<b>Flash point:</b>	> 232 °C (> 449.6 °F) ; Estimated
<b>Autoignition temperature:</b>	Not available
<b>Flammable/Explosive limits - lower:</b>	Not applicable
<b>Flammable/Explosive limits - upper:</b>	Not applicable
<b>Extinguishing media:</b>	Use extinguishing measures appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide.
<b>Special firefighting procedures:</b>	Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA). Wear full protective clothing.
<b>Unusual fire or explosion hazards:</b>	None
<b>Hazardous combustion products:</b>	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	No special environmental precautions required. Do not allow material to contaminate ground water system.
<b>Clean-up methods:</b>	Spilled material will solidify. Scrape up spilled material and place in a closed container for disposal.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Always be careful around molten material. Avoid skin contact with molten resins. Follow suggested application temperature. Do not wear contact lenses. At elevated temperatures, irritating fumes may be emitted. Provide adequate ventilation. Wash hands before breaks and immediately after handling the product.
<b>Storage:</b>	For safe storage, store between 0.0 °C (32°F) and 38.0 °C (100.4 °F)

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Paraffin waxes and Hydrocarbon waxes	2 mg/m <sup>3</sup> TWA Fume.	None	None	None

<b>Engineering controls:</b>	Work should be done in an adequately ventilated area (i.e., ventilation sufficient to maintain concentrations below one half of the PEL and other relevant standards). Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination.
<b>Respiratory protection:</b>	No personal respiratory protective equipment normally required. Where the potential exists for exposure to decomposition products due to heating or elevated temperatures, wear NIOSH approved respiratory protection as appropriate. Observe OSHA regulations for respiratory use (29 CFR 1910.134).
<b>Eye/face protection:</b>	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Do not wear contact lenses.
<b>Skin protection:</b>	Insulated gloves and long sleeved clothing are strongly recommended when working with molten adhesive.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Solid
<b>Color:</b>	Yellow
<b>Odor:</b>	Slight
<b>Odor threshold:</b>	Not available
<b>pH:</b>	not applicable
<b>Vapor pressure:</b>	Not available
<b>Boiling point/range:</b>	Not available
<b>Melting point/ range:</b>	110 °C (230°F) (Softening Point)
<b>Specific gravity:</b>	0.96
<b>Vapor density:</b>	Not available
<b>Flash point:</b>	> 232 °C (> 449.6 °F) ; Estimated
<b>Flammable/Explosive limits - lower:</b>	Not applicable
<b>Flammable/Explosive limits - upper:</b>	Not applicable
<b>Autoignition temperature:</b>	Not available
<b>Evaporation rate:</b>	Not applicable
<b>Solubility in water:</b>	Insoluble
<b>Partition coefficient (n-octanol/water):</b>	Not available
<b>VOC content:</b>	Negligible

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable
<b>Hazardous reactions:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Thermal decomposition can lead to release of irritating gases and vapors. carbon monoxide carbon dioxide
<b>Incompatible materials:</b>	Oxidizing agents.
<b>Conditions to avoid:</b>	To avoid thermal decomposition, do not overheat. Avoid temperatures above 200°C (392°F).

## 11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Paraffin waxes and Hydrocarbon waxes	No	No	No

Hazardous components	Health Effects/Target Organs
Paraffin waxes and Hydrocarbon waxes	Irritant

## 12. ECOLOGICAL INFORMATION

Ecological information: No data available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** This product is not a RCRA hazardous waste when discarded. Processing, use, or contamination of this product may change the hazard classification and waste management options. Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### Water Transportation (IMO/IMDG)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

## 15. REGULATORY INFORMATION

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
**TSCA 12(b) Export Notification:** None above reporting de minimus  
**CERCLA/SARA Section 302 EHS:** Not available  
**CERCLA/SARA Section 311/312:** None  
**CERCLA/SARA 313:** None above reporting de minimus  
**California Proposition 65:** No California Proposition 65 listed chemicals are known to be present.

### Canada Regulatory Information

**CEPA DSL/NDL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.  
**WHMIS hazard class:** Not controlled

## 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: First issue.

Prepared by: S. Fedele, Regulatory Affairs

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.